What is claim d is:

5

10

15

25

30

- 1. A wrap film comprising a layer of resin composition (C) as at least one surface layer, wherein resin composition (C) comprises 100 parts by mass of an aliphatic polyester resin (A) and 5 to 40 parts by mass of a liquid additive (B), having a surface roughness of 0.5 to 4.0 nm, a tensile modulus of 400 to 1500 MPa, a heat resistant temperature of 130 °C or more and cling energy of 0.5 to 2.5 mJ.
- 2. A wrap film roll comprising a core and the wrap film according to claim 1 wound around the core, wherein a pulling-out force of the wrap film from the core is 5 to 100 cN.
- 3. The wrap film according to claim 1, wherein the aliphatic polyester resin (A) contains 90 % by mass or more of polylactic acid resin comprising 8 % by mass or less of D-body.
- 4. The wrap film according to claim 1, wherein the liquid additive (B) contains 70 % by mass or more of glycerin fatty acid ester.
- 5. The wrap film according to claim 4, wherein the glycerin fatty acid ester is represented by the following formula (I).

Formula (I):

(wherein R^1 represents alkyl group, and R^2 and R^3 represents acetyl group or hydrogen.)

- 6. A wrap product comprising a core, the wrap film according to any one of claims 1 and 3 to 5 wound around the core and a box having the wrap film placed therein, wherein a cutter blade attached to the box is made of plant derivative-resin or paper.
- 7. A wrap product comprising the wrap film roll according to claim 2 and a box having the wrap film roll placed therein,

wherein a cutter blade attached to the box is made of plant derivative-resin or paper.